




WAC229 - HydroSlick SiO₂ Ceramic Wax

SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** WAC229 - HydroSlick SiO₂ Ceramic Wax
- Other means of identification:**
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses: Bodywork cleaning
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**
Chemical Guys
3501 Sepulveda Blvd
90505 Torrance - California - United States
Phone: 866-822-3670 - Fax: 310-988-1061
info@ChemicalGuys.com
www.ChemicalGuys.com
- 1.4 Emergency phone number:** 866-822-3670

SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
29 CFR 1910.1200:
While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
- 2.2 Label elements:**
29 CFR 1910.1200:
Hazard statements:
Not applicable (N/A)
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P501: Dispose of the contents/containers according to the local, state and federal regulations.
Additional labeling:
- 
- WARNING**
Keep out of the reach of children
This product can expose you to chemicals including Formaldehyde, Ethylbenzene, Cumene, which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.
- 2.3 Hazards not otherwise classified (HNOC):**
Not applicable (N/A)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substances:**
Non-applicable
- 3.2 Mixtures:**
Chemical description: Aqueous mixture composed of additives
Components:
According to APPENDIX D TO §1910.1200- Composition/information on ingredients, none of the substances which are classified as health hazards are present above their cut-off/concentration limits

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO₂ Ceramic Wax

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Consult a doctor in case of discomfort with this Safety data Sheet.

By inhalation:

In case of symptoms, move the person affected into fresh air.

By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse with water until the product has been eliminated. In case of problems, consult a doctor with the SDS of this product.

By ingestion/aspiration:

In case of consumption in large quantities, it is recommended to seek medical assistance.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable, low risk of fire by the inflammability characteristics of the product in normal conditions of storage, manipulation and use. In the case of the existence of sustained combustion as a result of improper manipulation, storage or use any type of extinguishing agent can be used (ABC Powder, water,...)

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, manipulation and use.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO₂ Ceramic Wax

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

It is recommended to transfer at a slow speed to avoid the creation of electrostatic charges that could affect flammable products. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is not necessary to take special measures to prevent environmental risks. For more information see subsection 6.2

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Not applicable (N/A)

D.- Eye and face protection

Not applicable (N/A)

E.- Bodily protection

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO₂ Ceramic Wax

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Not applicable (N/A)

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 68 °F:	Liquid
Appearance:	Transparent
Color:	 Blue
Odor:	Characteristic
Odour threshold:	Not applicable (N/A) *

Volatility:

Boiling point at atmospheric pressure:	213 °F
Vapour pressure at 68 °F:	2376 Pa
Vapour pressure at 122 °F:	12433.29 Pa (12.43 kPa)
Evaporation rate at 68 °F:	Not applicable (N/A) *

Product description:

Density at 68 °F:	1035.1 kg/m ³
Relative density at 68 °F:	1.035
Dynamic viscosity at 68 °F:	Not applicable (N/A) *
Kinematic viscosity at 68 °F:	Not applicable (N/A) *
Kinematic viscosity at 104 °F:	Not applicable (N/A) *
Concentration:	Not applicable (N/A) *
pH:	Not applicable (N/A) *
Vapour density at 68 °F:	Not applicable (N/A) *
Partition coefficient n-octanol/water 68 °F:	Not applicable (N/A) *
Solubility in water at 68 °F:	Not applicable (N/A) *
Solubility properties:	Not applicable (N/A) *
Decomposition temperature:	Not applicable (N/A) *
Melting point/freezing point:	Not applicable (N/A) *

Flammability:

Flash Point:	Non Flammable (>199.4 °F)
Flammability (solid, gas):	Not applicable (N/A) *
Autoignition temperature:	545 °F
Lower flammability limit:	Not applicable (N/A) *
Upper flammability limit:	Not applicable (N/A) *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO₂ Ceramic Wax

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Explosive properties:	Not applicable (N/A) *
Oxidising properties:	Not applicable (N/A) *
Corrosive to metals:	Not applicable (N/A) *
Heat of combustion:	Not applicable (N/A) *
Aerosols-total percentage (by mass) of flammable components:	Not applicable (N/A) *
Other safety characteristics:	
Surface tension at 68 °F:	Not applicable (N/A) *
Refraction index:	Not applicable (N/A) *

*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

LD50 oral > 5000 mg/kg (rat)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met
- Corrosivity/Irritability: Based on available data, the classification criteria are not met

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met
- Corrosivity/Irritability: Based on available data, the classification criteria are not met

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met
- Contact with the eyes: Based on available data, the classification criteria are not met

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO2 Ceramic Wax

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met
IARC: Formaldehyde (1); Stoddard solvent, < 0.1 % EC 200-753-7 (3); Xylene (3); Ethylbenzene (2B); Cumene (2B)
- Mutagenicity: Based on available data, the classification criteria are not met
- Reproductive toxicity: Based on available data, the classification criteria are not met

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met
- Skin: Based on available data, the classification criteria are not met

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met
- Skin: Based on available data, the classification criteria are not met

H- Aspiration hazard:

Based on available data, the classification criteria are not met

Other information:

Not applicable (N/A)

Specific toxicology information on the substances:

Not available

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Not available

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO2 Ceramic Wax

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:

- 14.1 UN number:** Not applicable (N/A)
14.2 UN proper shipping name: Not applicable (N/A)
14.3 Transport hazard class(es): Not applicable (N/A)
Labels: Not applicable (N/A)
14.4 Packing group, if applicable: Not applicable (N/A)
14.5 Marine pollutant: No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Physico-Chemical properties: see section 9
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

- 14.1 UN number:** Not applicable (N/A)
14.2 UN proper shipping name: Not applicable (N/A)
14.3 Transport hazard class(es): Not applicable (N/A)
Labels: Not applicable (N/A)
14.4 Packing group, if applicable: Not applicable (N/A)
14.5 Marine pollutant: No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Special regulations: Not applicable (N/A)
EmS Codes:
Physico-Chemical properties: see section 9
Limited quantities: Not applicable (N/A)
Segregation group: Not applicable (N/A)
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- 14.1 UN number:** Not applicable (N/A)
14.2 UN proper shipping name: Not applicable (N/A)
14.3 Transport hazard class(es): Not applicable (N/A)
Labels: Not applicable (N/A)
14.4 Packing group, if applicable: Not applicable (N/A)
14.5 Marine pollutant: No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Physico-Chemical properties: see section 9
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

SECTION 15: REGULATORY INFORMATION

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO₂ Ceramic Wax

SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *Formaldehyde (50-00-0)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Xylene (1330-20-7)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *Formaldehyde (50-00-0)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*
- CANADA-Domestic Substances List (DSL): *Silicic acid, lithium magnesium sodium salt (53320-86-8)*; *1,3-bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione (6440-58-0)*; *Formaldehyde (50-00-0)*; *Water (7732-18-5)*; *Glycerol (56-81-5)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Titanium tetraisopropanolate (546-68-9)*; *Xylene (1330-20-7)*; *2-ethylhexane-1,3-diol (94-96-2)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Hexamethyldisiloxane (107-46-0)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*; *Poly(dimethylsiloxane), viscosity 1000 cP (25°C) (63148-62-9)*
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *Formaldehyde (50-00-0) - U122*; *Xylene (1330-20-7) - U239*; *Ethylbenzene (100-41-4) - 1000 lb*; *Cumene (98-82-8) - U055*; *sodium hydroxide (1310-73-2) - 1000 lb*
- Hazardous Air Pollutants (Clean Air Act): *Formaldehyde (50-00-0)*; *Xylene (1330-20-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*
- Massachusetts RTK - Substance List: *Formaldehyde (50-00-0)*; *Glycerol (56-81-5)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Xylene (1330-20-7)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- Minnesota - Hazardous substances ERTK: *Formaldehyde (50-00-0)*; *Glycerol (56-81-5)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Xylene (1330-20-7)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- New Jersey Worker and Community Right-to-Know Act: *Formaldehyde (50-00-0)*; *Glycerol (56-81-5)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Xylene (1330-20-7)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- New York RTK - Substance list: *Formaldehyde (50-00-0)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Xylene (1330-20-7)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- NTP (National Toxicology Program): *Formaldehyde (50-00-0)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Cumene (98-82-8)*
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): *Formaldehyde (50-00-0)*
- Pennsylvania Worker and Community Right-to-Know Law: *Formaldehyde (50-00-0)*; *Glycerol (56-81-5)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Xylene (1330-20-7)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- Rhode Island - Hazardous substances RTK: *Formaldehyde (50-00-0)*; *Xylene (1330-20-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*
- The Toxic Substances Control Act (TSCA) : *Silicic acid, lithium magnesium sodium salt (53320-86-8)*; *1,3-bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione (6440-58-0)*; *Formaldehyde (50-00-0)*; *Water (7732-18-5)*; *Glycerol (56-81-5)*; *Stoddard solvent, < 0.1 % EC 200-753-7 (8052-41-3)*; *Titanium tetraisopropanolate (546-68-9)*; *Xylene (1330-20-7)*; *2-ethylhexane-1,3-diol (94-96-2)*; *Trimethylbenzene (25551-13-7)*; *Ethylbenzene (100-41-4)*; *Hexamethyldisiloxane (107-46-0)*; *Cumene (98-82-8)*; *sodium hydroxide (1310-73-2)*; *Poly(dimethylsiloxane), viscosity 1000 cP (25°C) (63148-62-9)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *Formaldehyde (50-00-0)*; *Xylene (1330-20-7)*; *Ethylbenzene (100-41-4)*; *Cumene (98-82-8)*

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

- CONTINUED ON NEXT PAGE -



WAC229 - HydroSlick SiO2 Ceramic Wax

SECTION 16: OTHER INFORMATION (continued)

29 CFR 1910.1200:

Not applicable (N/A)

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 7/19/2023

Revised: 6/24/2024

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET